



Description	Number of teeth	Type	Material	D _p (mm)	D _e (mm)	D _f (mm)	F (mm)	S (mm)	R (mm)	D _m (mm)	D _i (mm)	Taper bushing	Weight without bushing (=kg)
8M - Pitch 8 mm for belt width 20 mm													
TB 22 8M 20	22	5F	ST	56.02	54.65	60	28	22	6	-	37	1008	0.240
TB 24 8M 20	24	5F	ST	61.12	59.75	66	28	22	6	-	44	1108	0.300
TB 26 8M 20	26	5F	ST	66.21	64.84	70	28	22	6	-	45	1108	0.360
TB 28 8M 20	28	5F	ST	71.30	70.08	75	28	22	6	-	50	1108	0.440
TB 30 8M 20	30	5F	ST	76.39	75.13	83	28	22	6	-	58	1108	0.530
TB 32 8M 20	32	5F	ST	81.49	80.16	87	28	25	3	-	63	1610	0.420
TB 34 8M 20	34	5F	ST	86.58	85.22	91	28	25	3	-	64	1610	0.550
TB 36 8M 20	36	5F	ST	91.67	90.30	97	28	25	3	-	68	1610	0.680
TB 38 8M 20	38	5F	ST	96.77	95.39	102	28	25	3	-	72	1610	0.800
TB 40 8M 20	40	5F	ST	101.86	100.49	106	28	25	3	-	76	1610	1.000
TB 44 8M 20	44	8F	ST	112.05	110.67	120	28	32	4	93	-	2012	1.200
TB 48 8M 20	48	8F	ST	122.23	120.86	128	28	32	4	96	-	2012	1.600
TB 56 8M 20	56	8F	ST	142.60	141.23	150	28	32	4	110	-	2012	2.400
TB 64 8M 20	64	8WF	ST	162.97	161.60	168	28	32	4	110	137	2012	2.700
TB 72 8M 20	72	8WF	ST	183.35	181.97	192	28	32	4	110	158	2012	3.300
TB 80 8M 20	80	8W	GG	203.72	202.35	-	28	32	4	110	180	2012	3.500
TB 90 8M 20	90	8A	GG	229.18	227.81	-	28	32	4	110	204	2012	3.650
8M - Pitch 8 mm for belt width 30 mm													
TB 22 8M 30	22	5F	ST	56.02	54.65	60	38	22	16	-	37	1008	0.290
TB 24 8M 30	24	5F	ST	61.12	59.75	66	38	22	16	-	44	1108	0.380
TB 26 8M 30	26	5F	ST	66.21	64.84	70	38	22	16	-	44	1108	0.450
TB 28 8M 30	28	5F	ST	71.30	70.08	75	38	25	13	-	50	1210	0.500
TB 30 8M 30	30	3F	ST	76.39	75.13	83	38	38	-	-	-	1615	0.450
TB 32 8M 30	32	3F	ST	81.49	80.16	87	38	38	-	-	-	1615	0.590
TB 34 8M 30	34	3F	ST	86.58	85.22	91	38	38	-	-	-	1615	0.770
TB 36 8M 30	36	3F	ST	91.67	90.30	97	38	38	-	-	-	1615	0.960
TB 38 8M 30	38	3F	ST	96.77	95.39	102	38	38	-	-	-	1615	1.150
TB 40 8M 30	40	3F	ST	101.86	100.49	106	38	38	-	-	-	1615	1.340
TB 44 8M 30	44	4F	ST	112.05	110.67	120	38	32	3	-	86	2012	1.330
TB 48 8M 30	48	4F	ST	122.23	120.86	128	38	32	3	-	90	2012	1.780
TB 56 8M 30	56	4F	ST	142.60	141.23	150	38	32	3	-	110	2012	3.760
TB 64 8M 30	64	8F	ST	162.97	161.60	168	38	45	7	125	-	2517	4.200
TB 72 8M 30	72	8WF	ST	183.35	181.97	192	38	45	7	125	158	2517	4.300
TB 80 8M 30	80	8W	GG	203.72	202.35	-	38	45	7	125	180	2517	4.600
TB 90 8M 30	90	8A	GG	229.18	227.81	-	38	45	7	125	204	2517	5.000
TB 112 8M 30	112	8A	GG	285.21	283.83	-	38	45	7	125	254	2517	6.200
TB 144 8M 30	144	8A	GG	366.69	365.32	-	38	45	7	125	336	2517	9.000